

CEPSA ENGRANAJES HPX

Description



High-performance synthetic oil formulated with synthetic bases (PAO) and extreme pressure additives that provide excellent properties for multiple applications under severe working conditions, operating under heavy loads and at low speeds.

Applications

- Especially recommended for all types of steel industrial gears in closed crankcases, operating under severe service conditions and subject to high shock loads and constant or intermittent heavy stress, including those working at very high loading and low speed.
- They can be used in bath, splash or oil mist lubrication systems, operating under a wide range of temperatures.
- Recommended for use in components working at high temperatures, where a conventional oil can quickly become oxidized.
- Also suitable in those applications where there is risk of micro pitting.

Product performance

- Excellent thermal and chemical stability. Reduces the formation of lacquers, deposits and varnishes.
- High viscosity index and low pour point.
- Compatibility with elastomers and seals.
- Excellent anti-wear properties. Increases the service life of gears.
- Perfect miscibility with mineral oils.
- High resistance to degradation. Reduces oil consumption, increasing the periods between oil changes.
- High resistance to the formation of foams and water emulsions.

Specifications

- DIN 51517 Part 3 HLP
- AIST 224
- ISO 12925-1 Type CKC / CKD / CKS
- DAVID BROWN S1.53.106
- AGMA 9005-F16 AntiScuff
- FIVES CINCINNATI P-Specs

Typical Characteristics

| CHARACTERISTIC | UNITS | METHOD | CEPSA ENGRANAJES HPX | | | |
|------------------------------|-------|-------------|----------------------|-------|-------|-------|
| | | | 150 | 220 | 320 | 460 |
| ISO Grade | | | | | | |
| Density at 15°C | Kg/l | ASTM D-4052 | 0.849 | 0.857 | 0.858 | 0.853 |
| Flash Point, COC | °C | ASTM D-92 | 245 | 245 | 250 | 250 |
| Pour Point | °C | ASTM D-5950 | -51 | -48 | -45 | -42 |
| Viscosity at 40°C | cSt | ASTM D-445 | 144 | 212 | 309 | 447 |
| Viscosity at 100°C | cSt | ASTM D-445 | 20.8 | 25.3 | 34.3 | 46.1 |
| Viscosity Index | - | ASTM D-2270 | 169 | 151 | 156 | 160 |
| Timken OK Load (lb) | lb | LL-2782 | 65 | 70 | 70 | 70 |
| FZG Test, load failure stage | - | DIN 51354-2 | >12 | >12 | >12 | >12 |
| Four-ball test (D scar, max) | mm | ASTM D-2266 | 0.3 | 0.3 | 0.3 | 0.3 |
| (Load, min) | kg | ASTM D-2783 | 250 | 250 | 250 | 250 |

Health & Safety and Environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee.

These values may be modified without any prior warning.