

LUBRICANTS FOR INDUSTRIAL USE

CEPSA TRONCOIL BIOGAS LOW ASH

DESCRIPTION

Low-ash lubricant oil.

Formulated with highly refined, select paraffin base oils, with special, next-generation additives that are very effective at neutralizing highly corrosive acids which are found in the gas and inert to ammonia.

PRODUCT APPLICATIONS

- Especially formulated for engines fueled by gas derived from the anaerobic decomposition of urban waste, since its alkaline reserve (BN) and alkalinity retention are high enough to neutralize the chlorinated organic acids and hydrogen sulphide found in the gas.
- The product is ideal for use in modern engines designed with higher effective pressures, which are therefore more sensitive to ash and susceptible to the effects of detonation.
- The high retention of the alkaline reserve allows for longer oil-change intervals in the engines.

PRODUCT PERFORMANCE

- Balanced alkaline reserve with sufficient alkalinity retention. Superb neutralization of the acids formed by combustion.
- Remarkable resistance to corrosion and foam formation.
- Outstanding corrosion and oxidation stability.
- Superb protection against piston and jacket wear.
- Maximum protection of valves and seats.
- Resistant to the formation of carbonaceous residue and deposits, varnishes and sludge.
- Improved load service life.

SPECIFICATIONS

- Caterpillar
- GE Jenbacher TA 1000-1109 Series 2, 3, 4 and 6 – Gases B and C
- MAN
- MWM

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA TRONCOIL BIOGAS LOW ASH
SAE GRADE	-		40
Density, 15 °C	g/cc	D-4052	0.8727
Flash point, COC	°C, min.	D-92	>220
Pour point	°C	D-97	-30
Viscosity at 100 °C	cSt	D-445	13.35
Viscosity at 40 °C	cSt	D-445	120
Viscosity index	min.	D-2270	108
Base number	mg KOH/g	D-2896	4.5
Sulfated ash	% p	D-874	0.55

HEALTH & SAFETY AND ENVIRONMENT ENTE

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.