

STATEMENT OF CHARACTERISTICS

No. **C60B5 REC**

1. Name and identification code:

Cationic bituminous emulsion RECIEMUL C C60B5 REC CE

0099

2. Name and address of manufacturer:

CEPSA COMERCIAL PETRÓLEO, S.A. Pº de Castellana, nº 259 A – Torre CEPSA 28046 Madrid (Spain)

Tel.: + 34 91 337 60 00

https://www.cepsa.es/es/utilidades/catalogo/asfaltos

3. Expected use:

Cold recycling with emulsion

4. Characteristics performance assessment and verification system: 2+

5. Notified body:

AENOR 0099

• Task carried out: On-site factory assessment

• Assessment system: 2+

• Certificates: 0099/CPR/B11/0216 – Issue date: 30/7/2010

6. Stated characteristics:

Essential characteristics	Features	Harmonised technical specifications
Emulsion		
Creep time (2mm at 40°C)	Class 4	
Effect of water on the adhesive properties of the bonding agent (adhesion)	Class 3	
Break value	Class 5	
Recovered binder		
Consistency at intermediate service temperatures		
Penetration at 25°C	Class 5	EN 13808:2013
Consistency at high service temperatures		
Softening point	Class 8	
Stabilized binder (Stage I Durability)		
Consistency at intermediate service temperatures		
Penetration at 25°C	Class 4	
Consistency at high service temperatures		
Softening point	Class 7	



- The characteristics of the product identified in point 1 are in compliance with those declared in point 6.
- This statement of characteristics is issued under the sole responsibility of the manufacturer mentioned in point 2.
- Signed by and in representation of the manufacturer:

Gerardo Pardo Alvarez-Buylla

Managing Director of the Asphalt Unit CEPSA COMERCIAL PETRÓLEO, S.A.

Madrid, July 28, 2023