

LUBRICANTS FOR INDUSTRIAL USE CEPSA BLAMEDOL T-15



DESCRIPTION

Technical grade, medicinal white oil, for use in all processes requiring an additive-free white oil.

PRODUCT APPLICATIONS

- Generally, when it is recommended to use low-toxicity oil due to indirect or accidental contact with food and when compliance with pharmacopoeial specifications is not required.
- Recommending its use in the food industry, the animal feed industry, textiles, insecticides, rubber, cork specialities, plastics, precision instruments, etc.

PRODUCT PERFORMANCE

- Stability against light and heat.
- High viscosity index.
- Safe to handle.
- Usage concentrations according to FDA guidance.
- Compatible with mineral oil.
- Recommended for use in applications where there may be accidental contact with food.

SPECIFICATIONS

- NSF Nonfood Compounds Registration (H1)
- FDA 21 CFR 178.3620 (b)

TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	METHOD	CEPSA BLAMEDOL T-15
Density at 15°C	Kg/l	ASTM D-1298	0.85
Fire point V/A, min.	°C	ASTM D-92	180
Pour point, max.	°C	ASTM D-97	-9
Viscosity at 40°C	cSt	ASTM D-445	15
Ultraviolet absorption	-	21 CFR 178.3620 (b)	Pass

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.