

LUBRICANTS FOR INDUSTRIAL USE

CEPSA COMPRESORES LPG 9

DESCRIPTION

A synthetic fluid based on poly-alkyl-glycols.

PRODUCT APPLICATIONS

- Specially developed for the lubrication of gas compressors where the gearing and bearings operate under an atmosphere of gas such as: butane, propane, methane, ethylene, ammonia and vinyl chloride etc.

PRODUCT PERFORMANCE

- High antiwear strength. Lengthens equipment life.
- Low solubility in gases. Prolongs lubricant life.
- High detergent/dispersant characteristics. Guarantees equipment cleanliness.
- Excellent viscosity/temperature behaviour. Perfect lubrication at any temperature.

SPECIFICATIONS

- SULZER BURCKHARDT A.G. in type K compres
- LINDE A.G.

TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	METHOD	CEPSA COMPRESORES LPG 9
Density at 15°C	kg/l	ASTM D-4052	1,050
Fash Point COC	°C	ASTM D-92	>280
Pour Point, max.	°C	ASTM D-5950	<-36
Viscosity at 100°C	cSt	ASTM D-445	35
Viscosity at 40°C	cSt	ASTM D-445	185
Viscosity Index	-	ASTM D-2270	>230
Rusting		ASTM D-665A	Passes

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.