

LUBRICANT OILS FOR AGRICULTURAL MACHINERY

CEPSA AURIGA TE 55 10W30

DESCRIPTION

Universal multi-grade oil for tractor transmissions (UTTO) with the latest technology, fulfilling the requirements of modern agricultural equipment and suitable for use in wet brakes, hydraulic systems, clutches and torque converters.

PRODUCT APPLICATIONS

- High oxidation stability.
- Good antiwear and Extreme Pressure properties.
- Superb protection against corrosion and rust.
- High resistance to foam formation.
- Superb fluidity at low temperatures.
- Compatible with sealing materials.

PRODUCT PERFORMANCE

- Reduces the formation of sludge, lacquers and varnishes.
- High load capacity.
- Perfect lubrication at all operating speeds.
- Immediate oil circulation at start-up.
- No more vibration and screeching from brakes submerged in an oil bath.

SPECIFICATIONS

- API GL-4
- ZF TE-ML
- 03E/05F/06K/17E/21F^[1]
- KUBOTA UDT
- VOLVO CE WB-101
- Allison C3/C4
- MF CMS 1145/1143/1141/1135
- John Deere JDM J20C/D
- CAT TO-2
- FNHA-2C-201.00 (formerly FORD M2C-134D)
- CNH MAT 3525

[1] ZP – ZF001200

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA AURIGA TE 55
GRADO SAE		J300	10W30
Densidad 15°C	Kg/l	D-4052	0,8854
P. Inflamación V/A	°C	D-92	214
P. Congelación	°C	D-97	-32
Viscosidad a 100°C	cSt	D-445	9,60
Viscosidad a 40°C	cSt	D-445	56,46
Índice de Viscosidad		D-2270	155

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.