

CEPSA MOTO 4T RUTA 66 20W40



Description



Multi-grade high-performance mineral lubricant oil for four-stroke motorcycles used for city and open-road driving. Complies with the requirements of the main American, European and Japanese four-stroke motorcycle manufacturers.

Applications

- Recommended for four-stroke motorcycles of any capacity and performance, and for driving under severe conditions.
- Suitable for motorcycles with combined lubrication of the engine, gearbox and wet clutch. Also suitable for dry-clutch motorcycles.

Product Performance

- Its high detergency ensures excellent cleaning of the piston.
- Provides appropriate protection during start-up and high protection of the lubricant film at high temperatures.
- Excellent lubrication at all times of year, ensuring maximum protection against engine seizing.
- Protects the gears in the gear box, minimizing clutch plate slippage and loss of power.

Specifications

- API SL
- JASO MA2



JASO T903:2011 (MA2)
EL RENDIMIENTO ESTÁ GARANTIZADO POR:
CEPSA Comercial Petróleo S.A.U

Typical Characteristics

CHARACTERISTIC	UNITS	METHOD	CEPSA MOTO 4T RUTA 66
SAE Grade		---	20W40
Density at 15°C	g/ml	ASTM D4052	0.894
O/C Flash Point	°C	ASTM D92	223
Pour Point	°C	ASTM D5950	-27
Viscosity at 100°C	cSt	ASTM D445	13.79
Viscosity at 40°C	cSt	ASTM D445	121.9
Viscosity Index		ASTM D2270	111
Total Base Number (TBN)	mg KOH/g	ASTM D2896	6.9
Kinematic Viscosity at 100°C after Shear Stability Test	cSt	ASTM D6278	12.97

Health & Safety and Environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.