

MARINE LUBRICANTS

CEPSA CICONIA 30

DESCRIPTION

CEPSA CICONIA 30 oil has been developed to lubricate the crankcase of slow two-stroke marine diesel engines.

The product is formulated with highly refined base oils and has good anti-corrosion and anti-foaming properties. Its characteristics include a slight alkalinity, which helps neutralise acidic products resulting from combustion, which can enter the engine's crankcase cavity. It has a high degree of detergency and excellent oxidation stability, which ensures the cleanliness of the engine.

PRODUCT PERFORMANCE

- Excellent protection from wear and tear.
- Excellent detergent/dispersant properties, ensuring that the crankcase is cleaned.
- Protects all engine parts from corrosion.
- Prevents foams from forming.
- It has optimum characteristics to help clean the oil purifiers.

SPECIFICATIONS

- MAN B&W Diesel
- WÄRTSILÄ

TYPICAL CHARACTERISTICS

| CHARACTERISTIC | UNITS | ASTM STANDARD | CEPSA CICONIA 30 |
|--------------------|----------|---------------|------------------|
| SAE GRADE | | --- | 30 |
| Density at 15°C | kg/l | D-4052 | 0.894 |
| Flash point V/A | °C | D-92 | >220 |
| Freezing point, | °C | D-97 | -6 |
| Viscosity at 40°C | cSt | D-445 | 110 |
| Viscosity at 100°C | cSt | D-445 | 11.95 |
| Viscosity index | - | D-2270 | 96 |
| Base number, (min) | mg KOH/g | D-2896 | 5 |

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.