

MOTOR VEHICLE LUBRICANTS

CEPSA EP 90

DESCRIPTION

Mineral lubricant for manual gearboxes, differentials and automotive transmission gear assemblies in general that require extreme pressure (EP) properties.

PRODUCT APPLICATIONS

- Manual gearboxes in medium and heavy duty engines.
- Differentials, axles and final drives.
- Other mechanisms with automotive gear assemblies.

PRODUCT PERFORMANCE

- Excellent capacity to bear to shock loads
- Prevents metal-to-metal contact, controlling wear.
- Compatible with gearbox seals and elastomers.

SPECIFICATIONS

- API GL-5
 - MIL-PRF-2105-E
 - ZF TE-ML 07A/16C/17B/19B/21A ^[1]
 - MB-Approval 235.0
 - MAN 342 Type M1
 - Volvo 97310
- [1] – ZF 000097

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA EP 90
SAE grade			90
Density at 15°C	Kg/l	D-4052	0,903
Flash Point (COC)	°C	D-92	212
Pour Point	°C	D-97	<-18
Viscosity at 100°C	cSt	D-445	17.5
Viscosity at 40°C	cSt	D-445	189.7

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.