

MOTOR VEHICLE LUBRICANTS

CEPSA TRANSMISIONES 75W80



DESCRIPTION

Lubricant specially designed for manual gearboxes in passenger cars. Excellent thermal stability properties meeting the requirements of the main car manufacturers.

PRODUCT APPLICATIONS

- Manual gearboxes, whether synchronised or not.
- Good performance over a wide temperature range.
- Car steering and reduction units.
- Suitable for gearboxes in which GL-4 oils are required.

PRODUCT PERFORMANCE

- Excellent performance in cars at high speeds.
- Substantial reduction of metal wear.
- Good synchro engagement and durability.
- Does not attack joints and elastomers.
- Anticorrosive, compatible with materials.
- Thermal stability, oxidation resistance.
- Fluidity at low temperatures, reduced friction.

SPECIFICATIONS

- API GL-4
- API MT-1

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA TRANSMISIONES 75W80
SAE Grade			75W80
Density at 15°C	Kg/l	D-4052	0,895
Flash Point (COC)	°C	D-92	180
Pour Point	°C	D-97	-35
Viscosity at 100°C	cSt	D-445	8,5
Viscosity at -40°C	cSt	D-2983	<150.000
Corrosión al Cobre (3h., 100°C)	°C	D-130	1b

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.