

COOLANT



REFRIGERANT / ANTIFREEZE

CEPSA COOLANT

DESCRIPTION

Anti-freeze-Coolant for direct use, made from an ethylene glycol base and a high quality package of corrosion inhibitors provides complete protection for all the elements of the cooling circuit found in internal combustion engines. It does not contain amines, nitrites or phosphates.

PRODUCT APPLICATIONS

- As an anti-freeze coolant in internal combustion engines.
- Direct use. No dilution.
- Before adding the anti-freeze, the cooling circuit should be cleaned.

PRODUCT PERFORMANCE

- Excellent anti-corrosion protection for all the metals and alloys of the cooling circuit.
- Good anti-foam characteristics.
- High boiling point.
- Excellent cooling power.
- Excellent behaviour with gaskets and elastomers.
- Depending on concentration the product provides effective protection to:

CEPSA COOLANT 10%: -4°C

CEPSA COOLANT 20%: -9°C

CEPSA COOLANT 30%: -18°C

SPECIFICATIONS

• ASTM D-3306

• SAE J-1034

• BS 6580

• UNE 26.361.88

*Quality levels refer to concentrate product

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA COOLANT		
			10%	20%	30%
Aspect / Colour	-	Visual	Transparent / Fluorescent Yello		
Density at 20°C	g/cm ³	ASTM D-4052	1,015	1,030	1,045
Boiling Point	°C	ASTM D-1120	102	103	104
Pour Point	°C	ASTM D-3321	-4	-9	-18
pH	-	ASTM D-1287	8,3	8,3	8,3
Metal Corrosion	-	ASTM D-1384	Pass	Pass	Pass
Glycol content	% (w/w) min	UNE-26-361/2	10	20	30

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.